


Track Mounted Luminaire
RollIOS 33W LED



Luminaire: Adjustable track head with barn doors, integral; electronics LED driver and choice of IOS Reflector.

Materials: Die-cast aluminum with powder coat finish.

Adjustable: 356° horizontally, 145° vertically.

Installation - Track: Available for one, two circuit two neutral, or three circuit tracks, 120V only.

Installation - Surface Mount: GL3 heads may be installed on a monopoint adapter (SM) for installation over a standard 4" octagon fixture box.

Listing: ETL listed, Union assembled.

Reggiani reserves the right to change details without notice
GEN 2 REVISION 11/10/14

Driver

	Watts	Dimming	Max Power	AC input	Line Current	Power Factor
R02	33	n/a	34.3	120VAC	.34A	>90%

How To Specify

Trim	Lumen				Finish trim ring color	Driver	Track			Reflector	
	CCT	CRI	lumens	watt			Adaptor	Style	Circuit	IOS LL2 ▲	
38020.HQ	3000	97	2710lm	33	10 White	R02	G1	H	1 CCT	35050	16 Degrees
38020.WW	3000	82	3550lm	33	21 Black		GN	G	2H2N	35049	18 Degrees
38020.NN	4000	85	3560lm	33	28 Metallized Gray		G3	G	3 CCT	35051	28 Degrees
										35052	32 Degrees
										35053	46 Degrees
										35055	76 Degrees
										35054	Beam Elongator

trim/finish

driver

track

reflector

TYPE

Project Name: _____

Contact: _____ Date: _____